

Prod. N 121601

BEXOL DRACO GL-4 80W

Description	 This gear oil is a mineral lubricating oil for mechanical transmissions, formulated with high-quality solvent refined base oils and special EP-additives to obtain the following properties: a good resistance against oxidation good rust preventing, anti-corrosion and foam inhibiting properties a low pourpoint good Extreme Pressure (EP-) properties 	
Application	This gear oil should be used in hypoid differentials, gearboxes and other transmissions, for which an EP-transmission oil is advised.	
Performance Level	API GL-4 Mil-L-2105 Meets the requirements of MAN 341 Typ Z2/E1 MB 235.1 ZF TE-ML 17A	
Typicals	Density at 15 °C, kg/l Viscosity 40 °C, mm²/s Viscosity 100 °C, mm²/s Viscosity Index Flash Point COC, °C Pour Point, °C	0,879 77,00 9,50 98 205 -36

The data mentioned in this product information sheet are meant to enable the reader to orient himself about the properties and possible applications of our products. Although this overview is composed with all possible carefulness on the stated date, the composer does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, specially for critical applications, to make the final product-choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification. You can download a recent material safety data sheet of this product on our website.